

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number
WO 2004/109349 A2

(51) International Patent Classification⁷: G02B 5/32, 27/01

(21) International Application Number:
PCT/IL2004/000494

(22) International Filing Date: 9 June 2004 (09.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/477,699 10 June 2003 (10.06.2003) US

(71) Applicant (for all designated States except US): ELOP
ELECTRO-OPTICS INDUSTRIES LTD. [IL/IL]; P.O.
Box 1165, Kiryat Weizmann, 76111 Rehovot (IL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WEISS, Victor
[IL/IL]; 14 Pinsker Street, 72207 Rehovot (IL). GUR-
WICH, Joseph [IL/IL]; 25/29 Gilboa Street, 84746
Beer-Sheva (IL).

(74) Agent: KORAKH, Ellav; Borochoy, Korakh, Eliezeri &
Co., P.O. Box 58100, Kiryat Atidim, 61580 Tel Aviv (IL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND SYSTEM FOR DISPLAYING AN INFORMATIVE IMAGE AGAINST A BACKGROUND IMAGE



(57) Abstract: Incident image displaying device for displaying at least one incident image against a scene image of a scene, the incident image displaying device including at least one light guide, at least one input beam transforming element, at least one output beam transforming element being incorporated with a respective light guide, the scene image reflector being located behind the light guide, the input beam transforming element receiving incident light beams respective of the incident image from a respective one of at least one image source, the output beam transforming element being associated with a respective input beam transforming element, the scene image reflector reflecting the scene image through at least a portion of the output beam transforming element, wherein the input beam transforming element couples the incident light beams into the respective light guide as a set of coupled light beams, the set of coupled light beams is associated with the respective input beam transforming element, wherein the output beam transforming element receives from the respective light guide and decouples as decoupled light beams, the set of coupled light beams, thereby forming a set of output decoupled images, and wherein each output decoupled image of the set of output decoupled images is representative of a sensor fused image of the incident image.